

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 13686 (1993): Internal combustion engines - Radiators -
Method of test [TED 2: Automotive Primemovers]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



अंतर्दाही इंजन — विकिरक — परीक्षण पद्धति

Indian Standard

INTERNAL COMBUSTION ENGINES —
RADIATORS — METHODS OF TEST

UDC 621.43 : 629.113

© BIS 1993

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

August 1993

Price Group 1

FOREWORD

This Indian Standard was adopted by the Bureau of Indian Standards, after the draft finalized by the Automotive Primemovers Sectional Committee had been approved by the Transport Engineering Division Council.

This Indian Standard forms an important adjunct to the specification for radiators, IS 7611 : 1993.

The test procedures for pressure impulse, vibration would be further standardized after availability of data on equipment. The test such as bump test, test for paint and test for resistance to petrol etc, shall be optional and agreed to between the manufacturers and the suppliers.

IS 12996 : 1990 'Radiator pressure caps — Specification' is an important adjunct to this standard.

Heat dissipation performance test for radiators is covered separately in IS 13687 : 1993

In reporting the results of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'.

Indian Standard

INTERNAL COMBUSTION ENGINES — RADIATORS — METHODS OF TEST

1 SCOPE

1.1 This Indian Standard covers various test methods for radiators conforming to IS 7611 : 1993 'Internal combustion engines — Radiators — Specification (*first revision*)'.

2 REFERENCES

2.1 The following Indian Standards are necessary adjuncts to this standard.

<i>IS No.</i>	<i>Title</i>
13687 : 1993	Internal combustion engines — Radiators — Methods of test for heat dissipation performance
7611 : 1993	Internal combustion engines — Radiators — Specification (<i>first revision</i>)

3 TESTS

3.1 The tests shall consist of type and routine tests.

3.2 Type Tests

3.2.1 The following shall constitute the type tests:

- a) Visual examination (*see 3.5*),
- b) Pressure test (*see 3.6*),
- c) Leakage test for filler neck (*see 3.7*),
- d) Internal cleanliness test (*see 3.8*),
- e) Heat dissipation performance (*see 3.9*),
- f) Pressure impulse (*see 3.10*),
- g) Vibration (*see 3.11*), and
- h) Resistance to paint (*see 3.13*).

3.3 Routine Tests

3.3.1 The following tests shall be carried out on each radiator:

- a) Visual examination (*see 3.5*), and
- b) Pressure test (*see 3.6*).

3.4 Acceptance Tests

3.4.1 The following shall comprise of acceptance tests:

- a) Leakage test for radiator filler neck-cap (*see 3.7*);
- b) Internal cleanliness (*see 3.8*); and
- c) Dimensions (*see 3.12*).

3.5 Visual Examination

Each radiator shall be examined visually for workmanship and finish. The radiator shall be free from manufacturing defects such as dents, soldering defects.

3.6 Pressure Test

3.6.1 Procedure

The radiator is connected to a compressed air supply line. It is then immersed into a suitably sized water tank, kept full with water at normal ambient temperature. When subjected to internal air pressure at twice the cap pressure for one minute, the radiator shall reveal no leakage.

3.7 Leakage Test for Filler Necks

3.7.1 The test is carried out to assess the sealing efficiency at the neck seat. The radiator, complete with pressure cap is immersed into water at room temperature. A gradually increasing air pressure is applied to coolant ducts. The radiator shall show no leakage when the pressure is increased up to 5 kPa below the main valve opening pressure. The test shall be performed at both positions of filler cap.

3.8 Internal Cleanliness Test

3.8.1 The amount of chloride present in a cleaned core is assessed and calculated as the cleanliness of radiator.

3.8.2 Procedure

A total volume of water about one-third of the total radiator volume may be used for extraction of the chlorides present. The dry radiator is filled with half the computed volume with distilled water and shaken thoroughly for atleast ten minutes. The contaminated water is poured into a clean container. The procedure is repeated with the same quantity of water and the resultant is poured into the same container with the contaminated water. The amount of chloride present in the solution is determined by titrating with standard silver nitrate solution and a suitable indicator. The total chloride is calculated and expressed as weight in grams per litre of radiator volume capacity.

3.9 Heat Transfer Performance

3.9.1 This test shall be carried out in accordance with IS 13687 : 1993.

3.10 Pressure Impulse Test

3.10.1 The pressure impulse test shall be done between 1 and 1.5 times the operating pressure (relief valve setting) for 10 000 cycles with water in tank and air for cyclic pressure impulse. The cycle time shall be between 5 and 10 seconds.

3.11 Vibration Test

3.11.1 This test shall be carried out on a test rig, which vibrates in vertical direction. The radiator with water filled up at working pressure maintained at room temperature shall be mounted on the rig. The test is done along with mounting pad, mounting brackets as used on the vehicle under the following conditions:

Frequency, cycles/minute	— 1 440
Testing time in vertical direction	— 1 00 h
Amplitude	— 1.2 mm

3.12 Dimensions

3.12.1 The dimensions of the radiator filler neck shall comply with Table 1 and Fig. 10 of IS 7611 : 1993. The radiator volume shall be in accordance with the manufacturer's

recommendations and measured by filling up with water.

3.13 Resistance to Paint (Only for Painted Radiators)

3.13.1 Chequering Test

A representative specimen preferably flat, taken from top and bottom tank zone shall be subjected to the 'cheque pattern' test. This test shall be conducted by arranging a series of files held side by side. Incisions are made in the surface in two directions at right angles to each other. The painted surface shall not reveal any flaking or peeling.

3.13.2 Resistance to High Octane Petrol (Only for Newly Manufactured Engine Radiators)

Immerse a part of the radiator in high octane petrol for 30 minutes at room temperature. The paint film shall not dissolve or rankle, nor show blisters immediately after it is taken out of the bath.

3.13.3 Resistance to Corrosion (Only for Newly Manufactured Engine Radiators)

The radiator is exposed to a salt mist spray for 96 h. At the end of the period the radiator shall be thoroughly washed and examined for any corrosion. The edges of the internal sheet plating shall not reveal any signs of corrosion.

Standard Mark

The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards Monthly Additions'. Comments on this Indian Standard may be sent to BIS giving the following reference :

Doc : No. TED 2 (5233)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones : 331 01 31, 331 13 75

Telegrams : Manaksanstha
(Common to all Offices)

Regional Offices :

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 331 01 31 331 13 75
Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola CALCUTTA 700054	{ 37 84 99, 37 85 61 37 86 26, 37 86 62
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	{ 53 38 43, 53 16 40 53 23 84
Southern : C. I. T. Campus, IV Cross Road, MADRAS 600113	{ 235 02 16, 235 04 42 235 15 19, 235 23 15
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) BOMBAY 400093	{ 632 92 95, 632 78 58 632 78 91 632 78 92
Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. PATNA. THIRUVANANTHAPURAM.	